



ISO/IEC 19752 Yield Test Report

Part Number: 24015SA,
24035SA

E230, E232, E330, E332 Print Cartridge
Printer: E230

see below for additional part numbers

Declaration of **Average Cartridge Yield 2500 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 2843
Std Dev 145
90% Lower Confidence 2768

For questions concerning testing

contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA

Attn: Laser Supplies Product Manager

start 11-Jan-2005
stop 12-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake 2nd shake
Print mode	At fade At fade
Number of printers tested	Continuous
Media used	4
Paper feed orientation	Boise Cascade X-9 - 20# - Letter
Driver version	Short Edge Feed (SEF)
Operating system	9.3
Application software	Windows 2000
Test page version	Adobe Acrobat version 6.01 IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:	Printer	Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
		Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX043484242	38055MP	74	23	74	23	74	23	50	51	50	2,971	Yes
CAX043502784	38055MH	74	23	74	23	74	23	50	51	50	3,036	Yes
CAX043502780	38055BO	74	23	74	23	74	23	50	51	50	3,003	Yes
CAX043513480	380559C	74	23	74	23	74	23	50	51	50	2,861	Yes
CAX043513501	38055MP	74	23	74	23	74	23	50	51	50	2,619	Yes
CAX043484299	38055MH	74	23	74	23	74	23	50	51	50	2,895	Yes
CAX043502659	38055BO	74	23	74	23	74	23	50	51	50	2,643	Yes
CAX043502736	380559C	74	23	74	23	74	23	50	51	50	2,954	Yes
CAX043502719	38055MP	74	23	74	23	74	23	50	51	50	2,732	Yes
CAX043512736	38055MH	74	23	74	23	74	23	50	51	50	2,733	Yes
CAX043484303	38055BO	74	23	74	23	74	23	50	51	50	2,944	Yes
CAX043502733	380559C	74	23	74	23	74	23	50	51	50	2,727	Yes

Comments and or exceptions:

also covers:

12A8300	24018SL	34217HR
12A8400	24036SE	34237HR
24016SE	24037SR	SWE2500
24017SR	24038SL	