



**ISO/IEC 19752 Yield Test Report**

E260 3.5k Print Cartridge

Printer: E260

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>3500</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 4096  
**Std Dev** 195  
**90% Lower Confidence** 3976

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 6-Jun-2008      **stop** 9-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS08133A40	320011	70	21	71	22	69	21	55	60	52	3,929	Yes
CAS081331A45	320015	70	21	71	22	69	21	55	60	52	4,188	Yes
CAS081331A4A	320009	70	21	71	22	69	21	55	60	52	3,789	Yes
CAS081331A5B	320011	71	22	72	22	69	21	54	56	50	3,908	Yes
CAS081331A65	320015	71	22	72	22	69	21	54	56	50	4,239	Yes
CAS081331A6B	320009	71	22	72	22	69	21	54	56	50	4,099	Yes
CAS081331A4F	320011	71	22	72	22	69	21	54	56	50	4,429	Yes
CAS081331A63	320015	71	22	72	22	69	21	54	56	50	4,118	Yes
CAS081331A3B	320009	71	22	72	22	69	21	54	56	50	4,169	Yes

**Comments and or exceptions:**