



ISO/IEC 19752 Yield Test Report

Part Number: 24015SA,
24035SA

E230, E232, E330, E332 Print Cartridge
Printer: E330/E332

see below for additional part numbers

Declaration of **Average Cartridge Yield 2500 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 2777
Std Dev 96
90% Lower Confidence 2727

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start 11-Jan-2004 **stop** 12-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	9.3
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX043484298	38031GP	74	23	74	23	74	23	50	51	50	2,812	Yes
CAX043466557	380333Y	74	23	74	23	74	23	50	51	50	2,808	Yes
CAX043513464	38031NB	74	23	74	23	74	23	50	51	50	2,816	Yes
CAX043513509	38031NF	74	23	74	23	74	23	50	51	50	2,918	Yes
CAX043513497	38031GP	74	23	74	23	74	23	50	51	50	2,630	Yes
CAX043484319	380333Y	74	23	74	23	74	23	50	51	50	2,798	Yes
CAX043502695	38031NB	74	23	74	23	74	23	50	51	50	2,672	Yes
CAX043502728	38031NF	74	23	74	23	74	23	50	51	50	2,921	Yes
CAX043502663	38031GP	74	23	74	23	74	23	50	51	50	2,671	Yes
CAX043513352	380333Y	74	23	74	23	74	23	50	51	50	2,669	Yes
CAX043466635	38031NB	74	23	74	23	74	23	50	51	50	2,804	Yes
CAX043502667	38031NF	74	23	74	23	74	23	50	51	50	2,802	Yes

Comments and or exceptions:

Also covers:
 12A8300 24018SL 34217HR
 12A8400 24036SE 34237HR
 24016SE 24037SR SWE2500
 24017SR 24038SL