



ISO/IEC 19752 Yield Test Report

E340-E342n High Yield Print Cartridge

Printer: E340-E342n

Part Numbers: 34015HA 34016HE 34017HR 34018HL
 34035HA 34036HE 34037HR 34038HL
 12A8305 12A8405 34217XR

Declaration of Yield:	Average Cartridge Yield	6000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 7235
Std Dev 131
90% Lower Confidence 7167

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date tested	18-Jul-2005	20-Jul-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake 2nd shake
Print mode	At toner low At fade
Number of printers tested	Continuous
Media used	4
Paper feed orientation	Boise Cascade - 20# - Letter
Driver version	Short Edge Feed (SEF)
Operating system	E340-E342n G10
Application software	Windows 2000 Service Pack 4
Test page version	Acrobat version 7.0.2 19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAC051740210	MDT2122	77	25	77	25	76	24	55	57	54	7,411	Yes
CAC051740207	MDT2091	77	25	77	25	76	24	55	57	54	7,191	Yes
CAC051740223	MDT2104	77	25	77	25	76	24	55	57	54	7,331	Yes
CAC051740222	MDT2161	77	25	77	25	76	24	55	57	54	7,450	Yes
CAC051740093	MDT2122	75	24	77	25	74	23	56	59	52	7,131	Yes
CAC051740094	MDT2091	75	24	77	25	74	23	56	59	52	7,160	Yes
CAC051740103	MDT2104	75	24	77	25	74	23	56	59	52	7,221	Yes
CAC051740100	MDT2161	75	24	77	25	74	23	56	59	52	7,241	Yes
CAC051740227	MDT2122	75	24	76	24	74	23	57	59	55	7,099	Yes
CAC051740095	MDT2091	75	24	76	24	74	23	57	59	55	7,001	Yes
CAC051740219	MDT2104	75	24	76	24	74	23	57	59	55	7,331	Yes
CAC051740228	MDT2161	75	24	76	24	74	23	57	59	55	7,251	Yes

Comments and or exceptions: