



ISO/IEC 19752 Yield Test Report

E350d Ship With Equipment Print Cartridge

Printer: E350d

Declaration of Yield:	Average Cartridge Yield	1500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 2443
Std Dev 117
90% Lower Confidence 2371

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start stop
 11-Jul-2006 11-Jul-2006

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	E352dn G9
Operating system	Window XP
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS061531A1C	6203DDC	72	22	72	22	72	22	55	55	54	2,430	Yes
CAS061531A1F	6203DD5	72	22	72	22	72	22	55	55	54	2,469	Yes
CAS061531A34	6203DCP	72	22	72	22	72	22	55	55	54	2,480	Yes
CAS061531A1E	6203DDC	72	22	73	23	72	22	56	56	55	2,591	Yes
CAS061531A00	6203DD5	72	22	73	23	72	22	56	56	55	2,400	Yes
CAS061531A3A	6203DCP	72	22	73	23	72	22	56	56	55	2,290	Yes
CAS061531A22	6203DDC	73	23	73	23	73	23	56	56	56	2,289	Yes
CAS061531A44	6203DD5	73	23	73	23	73	23	56	56	56	2,629	Yes
CAS061531A03	6203DCP	73	23	73	23	73	23	56	56	56	2,410	Yes

Comments and or exceptions: