



ISO/IEC 19752 Yield Test Report

MB2236 Print Cartridge

Printer: MB2236adw

Declaration of Yield:	Average Cartridge Yield	1,200	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 1,258
Std Dev 1
90% Lower Confidence 1,257

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	26-Nov-2018	26-Nov-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark B2200 Series HBP ver 50_G4
Operating system		Windows 10
Application software		Adobe Acrobat Reader DC
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAG183090031	CFG-229-Mabolo	73	74	71	51	53	48	1,258	Y
	SCAG183090030	CFG-229-Mabolo	73	74	71	51	53	48	1,257	Y
	SCAG18309003B	CFG-229-Mabolo	73	74	71	51	53	48	1,259	Y
	SCAG183090032	CFS-055-Sambag	73	74	71	51	53	48	1,258	Y
	SCAG18309003A	CFS-055-Sambag	73	74	71	51	53	48	1,258	Y
	SCAG183090039	CFS-055-Sambag	73	74	71	51	53	48	1,256	Y
	SCAG18309002F	CFS-054-Santol	73	74	71	51	53	48	1,259	Y
	SCAG18309003C	CFS-054-Santol	73	74	71	51	53	48	1,258	Y
	SCAG18309002E	CFS-054-Santol	73	74	71	51	53	48	1,260	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) Generated test file have footer printed at every 200 pages.
- 3.) EOL was determined by the printer calling for the cartridge to be replaced