



ISO/IEC 19752 Yield Test Report

MB2236 High Yield Print Cartridge

Printer: MB2236adw

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,168
Std Dev 9
90% Lower Confidence 3,162

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	27-Nov-2018	28-Nov-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark B2200 Series HBP ver 50_G4
Operating system		Windows 10
Application software		Adobe Acrobat Reader DC
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAG183090021	CFG-229-Mabolo	73	75	73	51	53	48	3,170	Y
	SCAG18309002B	CFG-229-Mabolo	73	75	73	51	53	48	3,168	Y
	SCAG183090028	CFG-229-Mabolo	73	75	73	51	53	48	3,165	Y
	SCAG183090020	CFS-055-Sambag	73	75	73	51	53	48	3,170	Y
	SCAG183090022	CFS-055-Sambag	73	75	73	51	53	48	3,165	Y
	SCAG183090027	CFS-055-Sambag	73	75	73	51	53	48	3,159	Y
	SCAG18309002A	CFS-054-Santol	73	75	73	51	53	48	3,189	Y
	SCAG183090025	CFS-054-Santol	73	75	73	51	53	48	3,163	Y
	SCAG183090029	CFS-054-Santol	73	75	73	51	53	48	3,161	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) Generated test file have footer printed at every 200 pages.
- 3.) EOL was determined by the printer calling for the cartridge to be replaced.