



ISO/IEC 19752 Yield Test Report

MB2236 Extra High Yield Print Cartridge

Printer: MB2236adw

Declaration of Yield	Average Cartridge Yield	6,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 6,327
Std Dev 11
90% Lower Confidence 6,320

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	2-Jan-2019	8-Jan-2019
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark B2200 Series HBP ver 50_G4
Operating system		Windows 10
Application software		Adobe Acrobat Reader DC
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAG18352038A	CFG-229-Mabolo	73	74	72	50	54	48	6,314	Y
SCAG18352038C	CFG-229-Mabolo	73	74	72	50	54	48	6,327	Y
SCAG183520382	CFG-229-Mabolo	73	74	72	50	54	48	6,326	Y
SCAG183520389	CFS-055-Sambag	73	74	72	50	54	48	6,332	Y
SCAG183520386	CFS-055-Sambag	73	74	72	50	54	48	6,325	Y
SCAG183520385	CFS-055-Sambag	73	74	72	50	54	48	6,351	Y
SCAG183520388	CFS-054-Santol	73	74	72	50	54	48	6,311	Y
SCAG183520383	CFS-054-Santol	73	74	72	50	54	48	6,328	Y
SCAG183520387	CFS-054-Santol	73	74	72	50	54	48	6,326	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) Generated test file have footer printed at every 200 pages.
- 3.) EOL was determined by the printer calling for the cartridge to be replaced.