



ISO/IEC 19752 Yield Test Report

MB2338 Starter Print Cartridge

Printer: MB2338

Declaration of Yield	Average Cartridge Yield	2,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 2,324
Std Dev 111
90% Lower Confidence 2,255

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 11-Aug-2017	<u>stop</u> 14-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1717023AA	GSMPTB4600027	72	75	70	56	60	51	2,329	Y
CAS1717023BB	GSMPTB4600027	72	75	70	56	60	51	2,163	Y
CAS1717023B1	GSMPTB4600027	72	75	70	56	60	51	2,376	Y
CAS1717023B7	GSMPTB4600007	72	75	70	56	60	51	2,336	Y
CAS1717023B9	GSMPTB4600007	72	75	70	56	60	51	2,308	Y
CAS1717023B0	GSMPTB4600007	72	75	70	56	60	51	2,517	Y
CAS1717023B3	GSMPTB7017220	72	75	70	56	60	51	2,438	Y
CAS1717023AD	GSMPTB7017220	72	75	70	56	60	51	2,217	Y
CAS1717023A6	GSMPTB7017220	72	75	70	56	60	51	2,233	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.