



ISO/IEC 19752 Yield Test Report

MB2338 Print Cartridge

Printer: MB2338

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,368
Std Dev 150
90% Lower Confidence 3,275

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 15-Aug-2017	<u>stop</u> 18-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS17170242B	GSMPTB4600027	72	75	70	56	60	52	3,418	Y
	CAS17170241A	GSMPTB4600027	72	75	70	56	60	52	3,567	Y
	CAS171702424	GSMPTB4600027	72	75	70	56	60	52	3,294	Y
	CAS171702416	GSMPTB4600007	72	75	70	56	60	52	3,179	Y
	CAS1717023F2	GSMPTB4600007	72	75	70	56	60	52	3,314	Y
	CAS17170240B	GSMPTB4600007	72	75	70	56	60	52	3,203	Y
	CAS1717023F3	GSMPTB7017220	72	75	70	56	60	52	3,594	Y
	CAS1717023F4	GSMPTB7017220	72	75	70	56	60	52	3,461	Y
	CAS17170240F	GSMPTB7017220	72	75	70	56	60	52	3,282	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.