



ISO/IEC 19752 Yield Test Report

MB2442 Print Cartridge

Printer: MB2442

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,231
Std Dev 164
90% Lower Confidence 3,129

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 10-Aug-2017	<u>stop</u> 11-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS1717023EE	GSMPTB4600061	73	77	70	56	60	49	2,882	Y
	CAS17170241C	GSMPTB4600061	73	77	70	56	60	49	3,339	Y
	CAS1717023EF	GSMPTB4600061	73	77	70	56	60	49	3,238	Y
	CAS171702429	GSMPTB4600043	73	77	70	56	60	49	3,279	Y
	CAS171702423	GSMPTB4600043	73	77	70	56	60	49	3,262	Y
	CAS171702420	GSMPTB4600043	73	77	70	56	60	49	3,173	Y
	CAS1717023E8	GSMPTB7017257	73	77	70	56	60	49	3,121	Y
	CAS17170241D	GSMPTB7017257	73	77	70	56	60	49	3,468	Y
	CAS171702426	GSMPTB7017257	73	77	70	56	60	49	3,318	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.