



ISO/IEC 19752 Yield Test Report

MB2546 Extra High Yield Print Cartridge Printer MB2546

Declaration of Yield:	Average Cartridge Yield	10,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 10,495
Std Dev 212
90% Lower Confidence 10,364

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 6-Oct-2017	<u>stop</u> 7-Nov-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS172851967	GSMPTB4600074	73	77	70	56	60	49	10,980	Y
SCAS172851954	GSMPTB4600074	73	77	70	56	60	49	10,435	Y
SCAS17285195C	GSMPTB4600074	73	77	70	56	60	49	10,420	Y
CAS172851968	GSMPTB4600096	73	77	70	56	60	49	10,540	Y
SCAS172851951	GSMPTB4600096	73	77	70	56	60	49	10,340	Y
SCAS172851961	GSMPTB4600096	73	77	70	56	60	49	10,315	Y
CAS172851A38	GSMPTB7017325	73	77	70	56	60	49	10,600	Y
SCAS172851957	GSMPTB7017325	73	77	70	56	60	49	10,540	Y
SCAS17285195E	GSMPTB7017325	73	77	70	56	60	49	10,285	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.