



ISO/IEC 19752 Yield Test Report

MB2546 Print Cartridge

Printer: MB2546

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,365
Std Dev 97
90% Lower Confidence 3,306

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 15-Aug-2017	<u>stop</u> 17-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAS17170240D	GSMPTB4600074	73	77	70	56	60	49	3,508	Y
	SCAS1717023FF	GSMPTB4600074	73	77	70	56	60	49	3,278	Y
	SCAS1717023FD	GSMPTB4600074	73	77	70	56	60	49	3,408	Y
	SCAS171702401	GSMPTB4600096	73	77	70	56	60	49	3,308	Y
	SCAS171702402	GSMPTB4600096	73	77	70	56	60	49	3,285	Y
	SCAS1717023F5	GSMPTB4600096	73	77	70	56	60	49	3,328	Y
	SCAS171702417	GSMPTB7017325	73	77	70	56	60	49	3,357	Y
	SCAS171702410	GSMPTB7017325	73	77	70	56	60	49	3,531	Y
	SCAS1717023F6	GSMPTB7017325	73	77	70	56	60	49	3,286	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.