



# ISO/IEC 19752 Yield Test Report

## MB2650 Extra High Yield Print Cartridge Printer MB2650

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>10,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 10,238  
**Std Dev** 284  
**90% Lower Confidence** 10,062

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 3-Nov-2017	<u>stop</u> 7-Nov-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS172851967	GSMPTB4600074	73	77	70	56	60	49	9,935	Y
SCAS172851954	GSMPTB4600074	73	77	70	56	60	49	10,075	Y
SCAS17285195C	GSMPTB4600074	73	77	70	56	60	49	9,938	Y
CAS172851968	GSMPTB4600096	73	77	70	56	60	49	10,365	Y
SCAS172851951	GSMPTB4600096	73	77	70	56	60	49	10,150	Y
SCAS172851961	GSMPTB4600096	73	77	70	56	60	49	10,000	Y
CAS172851A38	GSMPTB7017325	73	77	70	56	60	49	10,670	Y
SCAS172851957	GSMPTB7017325	73	77	70	56	60	49	10,620	Y
SCAS17285195E	GSMPTB7017325	73	77	70	56	60	49	10,385	Y

### Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.