



# ISO/IEC 19752 Yield Test Report

## MB2650 Ultra High Yield Print Cartridge Printer MB2650

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>15,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 15,425  
**Std Dev** 451  
**90% Lower Confidence** 15,146

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date Tested</b>	12-Sep-2017	20-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS1717024C2	GSMPTB7018369	73	77	70	56	60	49	15,104	Y
SCAS17170252E	GSMPTB7018369	73	77	70	56	60	49	15,166	Y
SCAS171702514	GSMPTB7018369	73	77	70	56	60	49	15,251	Y
SCAS17170253A	GSMPTB4600160	73	77	70	56	60	49	15,410	Y
SCAS17170251A	GSMPTB4600160	73	77	70	56	60	49	14,663	Y
SCAS17170253C	GSMPTB4600160	73	77	70	56	60	49	15,678	Y
SCAS17170254B	GSMPTB4600134	73	77	70	56	60	49	15,607	Y
SCAS171702529	GSMPTB4600134	73	77	70	56	60	49	16,244	Y
SCAS171702515	GSMPTB4600134	73	77	70	56	60	49	15,703	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.