



# ISO/IEC 19752 Yield Test Report

## MB2650 Print Cartridge

Printer: MB2650

|                       |  |              |                       |
|-----------------------|--|--------------|-----------------------|
| Declaration of Yield: | <b>Average Cartridge Yield</b>                         | <b>3,000</b> | <b>Standard Pages</b> |
|                       | <b>Declared yield in accordance with ISO/IEC 19752</b> |              |                       |

**Average** 3,405  
**Std Dev** 134  
**90% Lower Confidence** 3,322

**For questions concerning testing contact**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

|  |  |                            |
|--|--|----------------------------|
| <b>Date Tested</b>                     | <u>start</u><br>14-Aug-2017            | <u>stop</u><br>16-Aug-2017 |
| Number of cartridges in testing        | 9                                      |                            |
| Qty. of cartridges used in calculation | 9                                      |                            |
| Shake Procedure                        | 1st shake                              | No Shake                   |
|  | 2nd shake                              | No Shake                   |
| Print mode                             | Continuous                             |                            |
| Number of printers tested              | 3                                      |                            |
| Media used                             | Hammermill Tidal MP - 20 lbs. - Letter |                            |
| Paper feed orientation                 | Short Edge Feed (SEF)                  |                            |
| Driver version                         | Lexmark MS520 XL Series                |                            |
| Operating system                       | Windows 7 Professional                 |                            |
| Application software                   | Acrobat version 9                      |                            |
| Test page version                      | ISO_IEC_19752_2004_Test_Page.pdf       |                            |
| Power (off/on) everyday                | ON                                     |                            |

| Cartridge testing data: | Cartridge     | Printer       | Temperature |     |     | Humidity |     |     | Cartridge Yield | Cart used in Calculation |
|-------------------------|---------------|---------------|-------------|-----|-----|----------|-----|-----|-----------------|--------------------------|
|                         |               |               | Avg         | Max | Min | Avg      | Max | Min |                 |                          |
|                         | SCAS171702415 | GSMPTB7018369 | 73          | 77  | 70  | 56       | 60  | 49  | 3,464           | Y                        |
|                         | SCAS171702427 | GSMPTB7018369 | 73          | 77  | 70  | 56       | 60  | 49  | 3,438           | Y                        |
|                         | SCAS1717023EA | GSMPTB7018369 | 73          | 77  | 70  | 56       | 60  | 49  | 3,083           | Y                        |
|                         | SCAS171702422 | GSMPTB4600160 | 73          | 77  | 70  | 56       | 60  | 49  | 3,504           | Y                        |
|                         | SCAS171702405 | GSMPTB4600160 | 73          | 77  | 70  | 56       | 60  | 49  | 3,339           | Y                        |
|                         | SCAS17170241E | GSMPTB4600160 | 73          | 77  | 70  | 56       | 60  | 49  | 3,545           | Y                        |
|                         | SCAS1717023E6 | GSMPTB4600134 | 73          | 77  | 70  | 56       | 60  | 49  | 3,440           | Y                        |
|                         | SCAS17170242A | GSMPTB4600134 | 73          | 77  | 70  | 56       | 60  | 49  | 3,419           | Y                        |
|                         | SCAS1717023E9 | GSMPTB4600134 | 73          | 77  | 70  | 56       | 60  | 49  | 3,410           | Y                        |

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.