



ISO/IEC 19752 Yield Test Report

MB2650 High Yield Print Cartridge Printer MB2650

Declaration of Yield:	Average Cartridge Yield	6,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 6,403
Std Dev 365
90% Lower Confidence 6,176

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 29-Sep-2017	<u>stop</u> 3-Oct-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS17236250C	GSMPTB7018369	73	77	70	56	60	49	6,471	Y
SCAS172362516	GSMPTB7018369	73	77	70	56	60	49	6,196	Y
SCAS172362530	GSMPTB7018369	73	77	70	56	60	49	6,138	Y
SCAS172362511	GSMPTB4600160	73	77	70	56	60	49	6,318	Y
SCAS172362523	GSMPTB4600160	73	77	70	56	60	49	6,526	Y
SCAS172362524	GSMPTB4600160	73	77	70	56	60	49	5,842	Y
SCAS172362528	GSMPTB4600134	73	77	70	56	60	49	6,838	Y
SCAS17236252F	GSMPTB4600134	73	77	70	56	60	49	7,036	Y
SCAS17236252C	GSMPTB4600134	73	77	70	56	60	49	6,259	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.