



ISO/IEC 19752 Yield Test Report

MB2765 Extra High Yield Print Cartridge Printer MB2765

Declaration of Yield:	Average Cartridge Yield	30,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 33,763
Std Dev 720
90% Lower Confidence 33,317

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 16-Jan-2018	<u>stop</u> 19-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210126	4064PTBGLA165	73	75	66	51	60	48	34,632	Y
CAS173210116	4064PTBGLA165	72	75	65	53	64	48	33,876	Y
CAS173210122	4064PTBGLA165	72	75	65	53	64	49	34,177	Y
CAS17321011C	4064PTBGLA166	73	75	67	51	60	48	33,014	Y
CAS17321010A	4064PTBGLA166	72	75	65	53	64	48	32,702	Y
CAS173210127	4064PTBGLA166	72	75	65	53	64	49	33,367	Y
CAS17321011B	4064PTBGLA173	73	75	67	51	60	48	34,893	Y
CAS173210129	4064PTBGLA173	72	75	65	53	64	48	33,729	Y
CAS173210115	4064PTBGLA173	72	75	65	53	64	49	33,478	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.