



ISO/IEC 19752 Yield Test Report

MB2770 High Yield Print Cartridge

Printer: MB2770

| | | | |
|-----------------------|--|---------------|-----------------------|
| Declaration of Yield: | Average Cartridge Yield | 15,000 | Standard Pages |
| | Declared yield in accordance with ISO/IEC 19752 | | |

Average 16,778
Std Dev 330
90% Lower Confidence 16,573

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

| | | |
|--|-----------------------------|--|
| Date Tested | <u>start</u> 22-Jan-2018 | <u>stop</u> 25-Jan-2018 |
| Number of cartridges in testing | | 9 |
| Qty. of cartridges used in calculation | | 9 |
| Shake Procedure | 1st shake 2nd shake | No Shake No Shake |
| Print mode | | Continuous |
| Number of printers tested | | 3 |
| Media used | | Hammermill Tidal MP - 20 lbs. - Letter |
| Paper feed orientation | | Short Edge Feed (SEF) |
| Driver version | | 47_G3 |
| Operating system | | Windows 7 Professional |
| Application software | | Adobe Acrobat version 9 |
| Test page version | | ISO_IEC_19752_2004_Test_Page.pdf |
| Power (off/on) everyday | | ON |

| Cartridge testing data: | Cartridge | Printer | Temperature | | | Humidity | | | Yield | Calculation |
|-------------------------|---------------|---------------|-------------|-----|-----|----------|-----|-----|--------|-------------|
| | | | Avg | Max | Min | Avg | Max | Min | | |
| | CAS1732100F9 | 4064PTBGLA162 | 73 | 76 | 72 | 51 | 53 | 49 | 16,398 | Y |
| | CAS1732100B2 | 4064PTBGLA162 | 73 | 76 | 72 | 50 | 53 | 48 | 16,559 | Y |
| | CAS1732100BB | 4064PTBGLA162 | 73 | 76 | 72 | 50 | 53 | 48 | 16,837 | Y |
| | CAS1732100D7 | 4064PTBGLA163 | 73 | 76 | 72 | 51 | 53 | 49 | 16,999 | Y |
| | CAS1732100A3 | 4064PTBGLA163 | 73 | 76 | 72 | 50 | 53 | 48 | 17,496 | Y |
| | CAS1732100ABF | 4064PTBGLA163 | 73 | 76 | 72 | 50 | 53 | 48 | 16,947 | Y |
| | CAS1732100F3 | 4064PTBGLA164 | 73 | 76 | 72 | 51 | 53 | 49 | 16,668 | Y |
| | CAS1732100A9 | 4064PTBGLA164 | 73 | 76 | 72 | 50 | 53 | 48 | 16,594 | Y |
| | CAS1732100AC | 4064PTBGLA164 | 73 | 76 | 72 | 50 | 53 | 48 | 16,522 | Y |

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.