



ISO/IEC 19752 Yield Test Report

MB2770 Extra High Yield Print Cartridge Printer MB2770

Declaration of Yield:	Average Cartridge Yield	30,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 32,951
Std Dev 1,199
90% Lower Confidence 32,208

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 16-Jan-2018	<u>stop</u> 19-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210121	4064PTBGLA162	73	75	67	51	60	48	34,737	Y
CAS173210123	4064PTBGLA162	72	75	65	53	64	48	34,371	Y
CAS17321011A	4064PTBGLA162	72	75	65	53	64	49	33,843	Y
CAS173210118	4064PTBGLA163	73	75	67	51	60	48	32,790	Y
CAS173210113	4064PTBGLA163	72	75	65	53	64	48	32,952	Y
CAS17321011D	4064PTBGLA163	72	75	65	53	64	49	32,785	Y
CAS173210120	4064PTBGLA164	73	75	67	51	60	48	32,203	Y
CAS173210128	4064PTBGLA164	72	75	65	53	64	48	31,042	Y
CAS173210124	4064PTBGLA164	72	75	65	53	64	49	31,840	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.