

MB3442 Starter Toner Cartridge

Printer: MB3442adw

Declaration of Yield:

Average Cartridge Yield	1,500	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 2,528
Std Dev 225
90% Lower Confidence 2,389

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 19-Oct-2019 stop 19-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192707FA1	701992400002G	72	73	71	53	54	50	2,620	Y
	SCAD192707F9B	701992400002G	72	73	71	53	54	50	2,160	Y
	SCAD192707FA3	701992400002G	72	73	71	53	54	50	2,280	Y
	SCAD192707FA2	701992400001N	72	73	71	53	54	50	2,665	Y
	SCAD192707F97	701992400001N	72	73	71	53	54	50	2,890	Y
	SCAD192707FA8	701992400001N	72	73	71	53	54	50	2,700	Y
	SCAD192707F9C	460192400003L	72	73	71	53	54	50	2,560	Y
	SCAD192707FA4	460192400003L	72	73	71	53	54	50	2,485	Y
	SCAD192707F95	460192400003L	72	73	71	53	54	50	2,395	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.