

## MB3442 Starter Toner Cartridge

Printer: MB3442adw

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>2,500</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 3,486  
**Std Dev** 85  
**90% Lower Confidence** 3,434

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start      stop  
 17-Oct-2019      18-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD192697F31	701992400002G	72	73	71	54	59	50	3,560	Y
SCAD192697EE3	701992400002G	72	73	71	54	59	50	3,465	Y
SCAD192699046	701992400002G	72	73	71	54	59	50	3,470	Y
SCAD192697F36	701992400001N	72	73	71	54	59	50	3,515	Y
SCAD192697D59	701992400001N	72	73	71	54	59	50	3,560	Y
SCAD192697F3A	701992400001N	72	73	71	54	59	50	3,565	Y
SCAD192697F3C	460192400003L	72	73	71	54	59	50	3,320	Y
SCAD192697F32	460192400003L	72	73	71	54	59	50	3,390	Y
SCAD192697F3B	460192400003L	72	73	71	54	59	50	3,530	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.