

MB3442 Extra High Yield Toner Cartridge

Printer: MB3442adw

Declaration of Yield:

Average Cartridge Yield	6,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 6,901
Std Dev 136
90% Lower Confidence 6,816

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 21-Oct-2019 stop 22-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192707FB3	460192400005D	73	75	71	54	57	48	6,875	Y
	SCAD192707FB1	460192400005D	73	75	71	54	57	48	6,855	Y
	SCAD192707FAE	460192400005D	73	75	71	54	57	48	6,725	Y
	SCAD192707FAA	460192400005C	73	75	71	54	57	48	6,975	Y
	SCAD192707FAD	460192400005C	73	75	71	54	57	48	6,980	Y
	SCAD192707FAB	460192400005C	73	75	71	54	57	48	7,010	Y
	SCAD192707FB7	7019924000009	73	75	71	54	57	48	7,125	Y
	SCAD192707FAF	7019924000009	73	75	71	54	57	48	6,705	Y
	SCAD192707FB2	7019924000009	73	75	71	54	57	48	6,855	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the print starvation or fade.