



ISO/IEC 19798 Yield Test Report

MC3224 Starter Return Program Toner Cartridge

Printer: MC3224dwe / MC3224adwe

Part Numbers of Cartridges:

Cyan (C) 40NCC05C

Yellow (Y) 40NCC05Y

Magenta (M) 40NCC05M

Black (K) 40NCC08K

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield	500	standard pages
Average Continuous Black (K) Cartridge Yield	750	standard pages
Declared yield in accordance with ISO/IEC 19798		

Tested Cartridge Summary:

90% Lower Confidence
Composite Color (CMY) = **579** pages
Black = **783** pages

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested

	9-Jul-2019	10-Jul-2019			
Number of cartridges in testing		C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation		C= 9	M= 9	Y= 9	K= 9
Type of cartridge		One piece			
Shake Procedure		No Shake			
1st shake		No Shake			
2nd shake		Continuous			
Print mode		3			
Number of printers tested		Hammermill Tidal MP - 20 lbs. - Letter			
Media used		Short Edge Feed (SEF)			
Paper feed orientation		Golden			
Driver version		WINDOWS10			
Operating system		Adobe Reader 2018.009.20050			
Application software		ISO-IEC_24712_Test_suite-_v2.pdf			
Test page version		Y			
Power (off/on) everyday		Y			
Pre-generated file used		Y			
Header / Footer used		Y			
Computer Model		Dell Latitude 7490			
Computer RAM and CPU type		16GB Intel(R) Core™ i7-8650U CPU @ 1.90 GHz 2.11GHz			
PC / Printer connection		Network			

Comments :

EOL was determined at the onset of fade on printed page.



ISO/IEC 19798 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg	Max	Min	Avg	Max	Min		
1500921000D8	C	SCAD191689406	22 / 72	22 / 72	22 / 72	45	45	45	680	Y
1500921000D8	C	SCAD19168941B	22 / 72	22 / 72	22 / 72	45	45	45	615	Y
1500921000D8	C	SCAD19168940B	22 / 72	22 / 72	22 / 72	45	45	45	745	Y
350092100096	C	SCAD19168941A	22 / 72	22 / 72	22 / 72	45	45	45	510	Y
350092100096	C	SCAD191689420	22 / 72	22 / 72	22 / 72	45	45	45	665	Y
350092100096	C	SCAD19168940C	22 / 72	22 / 72	22 / 72	45	45	45	665	Y
1500921000C8	C	SCAD19168940A	22 / 72	22 / 72	22 / 72	45	45	45	690	Y
1500921000C8	C	SCAD191689526	22 / 72	22 / 72	22 / 72	45	45	45	670	Y
1500921000C8	C	SCAD19168941C	22 / 72	22 / 72	22 / 72	45	45	45	725	Y
1500921000D8	K	SCAD191663EC5	22 / 72	22 / 72	22 / 72	45	45	45	850	Y
1500921000D8	K	SCAD191663EC6	22 / 72	22 / 72	22 / 72	45	45	45	780	Y
1500921000D8	K	SCAD191663EC2	22 / 72	22 / 72	22 / 72	45	45	45	820	Y
350092100096	K	SCAD191663EB4	22 / 72	22 / 72	22 / 72	45	45	45	770	Y
350092100096	K	SCAD191663EAD	22 / 72	22 / 72	22 / 72	45	45	45	820	Y
350092100096	K	SCAD191663EC3	22 / 72	22 / 72	22 / 72	45	45	45	755	Y
1500921000C8	K	SCAD191663EAC	22 / 72	22 / 72	22 / 72	45	45	45	725	Y
1500921000C8	K	SCAD191663EC4	22 / 72	22 / 72	22 / 72	45	45	45	855	Y
1500921000C8	K	SCAD191663EC0	22 / 72	22 / 72	22 / 72	45	45	45	755	Y
1500921000D8	M	SCAD191689403	22 / 72	22 / 72	22 / 72	45	45	45	565	Y
1500921000D8	M	SCAD19168940F	22 / 72	22 / 72	22 / 72	45	45	45	615	Y
1500921000D8	M	SCAD1916893FD	22 / 72	22 / 72	22 / 72	45	45	45	650	Y
350092100096	M	SCAD191689402	22 / 72	22 / 72	22 / 72	45	45	45	775	Y
350092100096	M	SCAD191689415	22 / 72	22 / 72	22 / 72	45	45	45	610	Y
350092100096	M	SCAD191689414	22 / 72	22 / 72	22 / 72	45	45	45	510	Y
1500921000C8	M	SCAD191689416	22 / 72	22 / 72	22 / 72	45	45	45	655	Y
1500921000C8	M	SCAD191689412	22 / 72	22 / 72	22 / 72	45	45	45	590	Y
1500921000C8	M	SCAD191689413	22 / 72	22 / 72	22 / 72	45	45	45	775	Y
1500921000D8	Y	SCAD191663EA2	22 / 72	22 / 72	22 / 72	45	45	45	690	Y
1500921000D8	Y	SCAD191663E90	22 / 72	22 / 72	22 / 72	45	45	45	655	Y
1500921000D8	Y	SCAD191663E8D	22 / 72	22 / 72	22 / 72	45	45	45	695	Y
350092100096	Y	SCAD191663E94	22 / 72	22 / 72	22 / 72	45	45	45	580	Y
350092100096	Y	SCAD191663EA7	22 / 72	22 / 72	22 / 72	45	45	45	595	Y
350092100096	Y	SCAD191663EA5	22 / 72	22 / 72	22 / 72	45	45	45	630	Y
1500921000C8	Y	SCAD191663EA8	22 / 72	22 / 72	22 / 72	45	45	45	510	Y
1500921000C8	Y	SCAD191663EBD	22 / 72	22 / 72	22 / 72	45	45	45	510	Y
1500921000C8	Y	SCAD191663E8F	22 / 72	22 / 72	22 / 72	45	45	45	655	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Cyan Cartridge	663	68	620
Magenta Cartridge	638	89	583
Yellow Cartridge	613	70	570
CMY Composite			590
Black Cartridge	792	46	764