



ISO/IEC 19798 Yield Test Report

CX331 / MC3326 Starter Return Program Toner Cartridge

Printer: CX331adwe / MC3326adwe

Part Numbers of Cartridges:

Cyan (C) 40NCL05C

Yellow (Y) 40NCL05Y

Magenta (M) 40NCL05M

Black (K) 40NCL08K

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield	500	standard pages
Average Continuous Black (K) Cartridge Yield	750	standard pages
Declared yield in accordance with ISO/IEC 19798		

Tested Cartridge Summary:

90% Lower Confidence
Composite Color (CMY) = **579** pages
Black = **783** pages

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested

	10-Jul-2019	11-Jul-2019			
Number of cartridges in testing		C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation		C= 9	M= 9	Y= 9	K= 9
Type of cartridge		One piece			
Shake Procedure		No Shake			
1st shake		No Shake			
2nd shake		Continuous			
Print mode		3			
Number of printers tested		Hammermill Tidal MP - 20 lbs. - Letter			
Media used		Short Edge Feed (SEF)			
Paper feed orientation		Golden			
Driver version		WINDOWS10			
Operating system		Adobe Reader 2018.009.20050			
Application software		ISO-IEC_24712_Test_suite-_v2.pdf			
Test page version		Y			
Power (off/on) everyday		Y			
Pre-generated file used		Y			
Header / Footer used		Y			
Computer Model		Dell Latitude 7490			
Computer RAM and CPU type		16GB Intel(R) Core™ i7-8650U CPU @ 1.90 GHz 2.11GHz			
PC / Printer connection		Network			

Comments :

EOL was determined at the onset of fade on printed page.

ISO/IEC 19798 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg	Max	Min	Avg	Max	Min		
3500921000GW	C	SCAD191689406	22 / 72	22 / 72	22 / 72	45	45	45	700	Y
3500921000CW	C	SCAD19168941B	22 / 72	22 / 72	22 / 72	45	45	45	565	Y
3500921000GW	C	SCAD19168940B	22 / 72	22 / 72	22 / 72	45	45	45	570	Y
3500921000GW	C	SCAD19168941A	22 / 72	22 / 72	22 / 72	45	45	45	610	Y
3500921000CW	C	SCAD191689420	22 / 72	22 / 72	22 / 72	45	45	45	620	Y
3500921000CW	C	SCAD19168940C	22 / 72	22 / 72	22 / 72	45	45	45	560	Y
3500921000GP	C	SCAD19168940A	22 / 72	22 / 72	22 / 72	45	45	45	660	Y
3500921000GP	C	SCAD191689526	22 / 72	22 / 72	22 / 72	45	45	45	585	Y
3500921000GP	C	SCAD19168941C	22 / 72	22 / 72	22 / 72	45	45	45	505	Y
3500921000GW	K	SCAD191663EC5	22 / 72	22 / 72	22 / 72	45	45	45	910	Y
3500921000GW	K	SCAD191663EC6	22 / 72	22 / 72	22 / 72	45	45	45	835	Y
3500921000CW	K	SCAD191663EC2	22 / 72	22 / 72	22 / 72	45	45	45	850	Y
3500921000CW	K	SCAD191663EB4	22 / 72	22 / 72	22 / 72	45	45	45	750	Y
3500921000CW	K	SCAD191663EAD	22 / 72	22 / 72	22 / 72	45	45	45	765	Y
3500921000GP	K	SCAD191663EC3	22 / 72	22 / 72	22 / 72	45	45	45	750	Y
3500921000GP	K	SCAD191663EAC	22 / 72	22 / 72	22 / 72	45	45	45	795	Y
3500921000GP	K	SCAD191663EC4	22 / 72	22 / 72	22 / 72	45	45	45	840	Y
3500921000GW	K	SCAD191663EC0	22 / 72	22 / 72	22 / 72	45	45	45	860	Y
3500921000GW	M	SCAD191689403	22 / 72	22 / 72	22 / 72	45	45	45	565	Y
3500921000GW	M	SCAD19168940F	22 / 72	22 / 72	22 / 72	45	45	45	590	Y
3500921000CW	M	SCAD1916893FD	22 / 72	22 / 72	22 / 72	45	45	45	760	Y
3500921000CW	M	SCAD191689402	22 / 72	22 / 72	22 / 72	45	45	45	670	Y
3500921000CW	M	SCAD191689415	22 / 72	22 / 72	22 / 72	45	45	45	615	Y
3500921000GP	M	SCAD191689414	22 / 72	22 / 72	22 / 72	45	45	45	600	Y
3500921000GP	M	SCAD191689416	22 / 72	22 / 72	22 / 72	45	45	45	575	Y
3500921000GP	M	SCAD191689412	22 / 72	22 / 72	22 / 72	45	45	45	635	Y
3500921000GW	M	SCAD191689413	22 / 72	22 / 72	22 / 72	45	45	45	575	Y
3500921000GW	Y	SCAD191663EA2	22 / 72	22 / 72	22 / 72	45	45	45	540	Y
3500921000GW	Y	SCAD191663E90	22 / 72	22 / 72	22 / 72	45	45	45	590	Y
3500921000GW	Y	SCAD191663E8D	22 / 72	22 / 72	22 / 72	45	45	45	620	Y
3500921000CW	Y	SCAD191663E94	22 / 72	22 / 72	22 / 72	45	45	45	640	Y
3500921000CW	Y	SCAD191663EA7	22 / 72	22 / 72	22 / 72	45	45	45	590	Y
3500921000CW	Y	SCAD191663EA5	22 / 72	22 / 72	22 / 72	45	45	45	665	Y
3500921000GP	Y	SCAD191663EA8	22 / 72	22 / 72	22 / 72	45	45	45	630	Y
3500921000GP	Y	SCAD191663EBD	22 / 72	22 / 72	22 / 72	45	45	45	695	Y
3500921000GP	Y	SCAD191663E8F	22 / 72	22 / 72	22 / 72	45	45	45	635	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Cyan Cartridge	597	58	561
Magenta Cartridge	621	62	582
Yellow Cartridge	623	45	595
CMY Composite			579
Black Cartridge	817	55	783