



ISO/IEC 19752 Yield Test Report

MS310 Ship With Equipment Print Cartridge

Printer MS315dn

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 3,963
Std Dev 219
90% Lower Confidence 3,827

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	18-Jul-2013	19-Jul-2013
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Beta 1
Operating system		Windows XP SP3 (Version 2002)
Application software		Acrobat version 9.5.4
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
SCAS1313366EB	451432LM0LHZR	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	4,222	Y
SCAS131336701	451432LM0LHZR	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	3,870	Y
SCAS1313366FB	451432LM0LHZR	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	3,828	Y
SCAS1313366E2	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	4,111	Y
SCAS1313366DE	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	3,777	Y
SCAS1313366FD	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	3,661	Y
SCAS1313366E6	451432LM0LHZL	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	4,290	Y
SCAS1313366D4	451432LM0LHZL	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	3,824	Y
SCAS1313366FE	451432LM0LHZL	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	4,083	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.