



ISO/IEC 19752 Yield Test Report

MS310 High Yield Print Cartridge Printer MS315dn

Declaration of Yield:

Average Cartridge Yield	5,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 6,214
Std Dev 241
90% Lower Confidence 6,064

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 25-Jul-2013	<u>stop</u> 26-Jul-2013
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 3
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
SCAS122194DFA	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,246	Y
SCAS122194E23	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,236	Y
SCAS122194DF7	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,083	Y
SCAS12354527E	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,643	Y
SCAS122194DEB	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,247	Y
SCAS122194E17	451432LM0LHZG	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	5,761	Y
SCAS122194E0D	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,415	Y
SCAS122194DFE	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,208	Y
SCAS122194E0F	451432LM0LHZZ	72 / 22.2	73 / 22.8	71 / 21.7	53	56	49	6,084	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.