



ISO/IEC 19752 Yield Test Report

MS317 Print Cartridge

Printer: MS317

Declaration of Yield: **Average Cartridge Yield 2,500 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 4,129
Std Dev 452
90% Lower Confidence 3,849

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 1-May-2012	<u>stop</u> 2-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	(S)CAS1205970F7	4514PTB300383	71	73	70	53	56	49	4,118	Y
	(S)CAS120586F55	4514PTB300383	71	73	70	53	56	49	4,002	Y
	(S)CAS120586F6C	4514PTB300383	71	73	70	53	56	49	3,925	Y
	(S)CAS1205970F0	4514PTB300401	71	73	70	53	56	49	3,938	Y
	(S)CAS1205970F2	4514PTB300401	71	73	70	53	56	49	3,679	Y
	(S)CAS120586F6B	4514PTB300401	71	73	70	53	56	49	3,917	Y
	(S)CAS120586F54	4514PTB300403	71	73	70	53	56	49	4,157	Y
	(S)CAS120586F5A	4514PTB300403	71	73	70	53	56	49	4,164	Y
	(S)CAS120586F4D	4514PTB300403	71	73	70	53	56	49	5,264	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.