

MS331 High Yield Toner Cartridge

Printer: MS331dn

Declaration of Yield:

Average Cartridge Yield	15,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 15,512
Std Dev 346
90% Lower Confidence 15,297

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 22-Oct-2019 stop 29-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake
Number of printers tested	No shake
Media used	Continuous
Paper feed orientation	3
Driver version	Hammermill Tidal MP - 20 lbs. - Letter
Operating system	Short Edge Feed (SEF)
Application software	Lexmark Printer Software G4 v1.2
Test page version	Windows 7 Professional
	Adobe Acrobat version 9
	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
Cartridge	Printer								
SCAD192707F8D	460192400005D	73	75	71	53	58	48	15,235	Y
SCAD192707F82	460192400005D	73	75	71	53	58	48	15,090	Y
SCAD192707F87	460192400005D	73	75	71	53	58	48	15,385	Y
SCAD192707F83	460192400005C	73	75	71	53	58	48	16,045	Y
SCAD192707F8C	460192400005C	73	75	71	53	58	48	15,780	Y
SCAD192707F8F	460192400005C	73	75	71	53	58	48	15,785	Y
SCAD192707F86	7019924000009	73	75	71	53	58	48	15,740	Y
SCAD192707F89	7019924000009	73	75	71	53	58	48	15,060	Y
SCAD192707F92	7019924000009	73	75	71	53	58	48	15,485	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the print starvation or fade.