



ISO/IEC 19752 Yield Test Report

MS410 High Yield Print Cartridge Printer MS415dn

Declaration of Yield:

Average Cartridge Yield	5,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 6,519
Std Dev 329
90% Lower Confidence 6,317

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 15-May-2012	<u>stop</u> 17-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS120586A6C	4514PTB300139	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,932	Y
(S)CAS120586A4E	4514PTB300139	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,835	Y
(S)CAS120586F69	4514PTB300139	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,575	Y
(S)CAS120586A4B	4514PTB300117	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,712	Y
(S)CAS120586A4F	4514PTB300117	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,748	Y
(S)CAS120586A43	4514PTB300117	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,483	Y
(S)CAS120586F42	4514PTB300307	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,112	Y
(S)CAS120586F40	4514PTB300307	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,251	Y
(S)CAS120586F86	4514PTB300307	72 / 22.2	75 / 23.9	68 / 20	46	49	42	6,021	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.