



ISO/IEC 19752 Yield Test Report

MS410 Extra High Yield Print Cartridge Printer MS415dn

Declaration of Yield:	Average Cartridge Yield	10,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 12,399
Std Dev 696
90% Lower Confidence 11,967

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 19-Apr-2012	<u>stop</u> 23-Apr-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1205869AE	4514PTB300139	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	13,425	Y
(S)CAS120586A3A	4514PTB300139	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	12,383	Y
(S)CAS120586913	4514PTB300139	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	11,886	Y
(S)CAS1205869F8	4514PTB300117	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	12,455	Y
(S)CAS1205869A6	4514PTB300117	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	11,896	Y
(S)CAS1205869FA	4514PTB300117	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	11,492	Y
(S)CAS1205869B3	4514PTB300145	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	13,564	Y
(S)CAS1205869A5	4514PTB300145	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	12,442	Y
(S)CAS120586A0C	4514PTB300145	71 / 21.7	76 / 24.4	70 / 21.1	55	63	48	12,046	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.