

MS431 High Yield Toner Cartridge

Printer: MS431dn/dw

Declaration of Yield:

Average Cartridge Yield	15,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 15,909
Std Dev 363
90% Lower Confidence 15,684

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 21-Oct-2019 stop 25-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake
Number of printers tested	No shake
Media used	Continuous
Paper feed orientation	3
Driver version	Hammermill Tidal MP - 20 lbs. - Letter
Operating system	Short Edge Feed (SEF)
Application software	Lexmark Printer Software G4 v1.2
Test page version	Windows 7 Professional
	Adobe Acrobat version 9
	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192707F94	701992400002G	73	75	71	53	58	48	15,530	Y
	SCAD192707F84	701992400002G	73	75	71	53	58	48	16,600	Y
	SCAD192707F90	701992400002G	73	75	71	53	58	48	16,150	Y
	SCAD192707F85	701992400001N	73	75	71	53	58	48	15,635	Y
	SCAD192707F8B	701992400001N	73	75	71	53	58	48	15,660	Y
	SCAD192707F8E	701992400001N	73	75	71	53	58	48	16,085	Y
	SCAD192707F8A	460192400003L	73	75	71	53	58	48	16,020	Y
	SCAD192707F81	460192400003L	73	75	71	53	58	48	16,020	Y
	SCAD192707F93	460192400003L	73	75	71	53	58	48	15,480	Y

Comments and or exceptions: