

MS431 Toner Cartridge

Printer: MS431dn/dw

Declaration of Yield:

Average Cartridge Yield	3,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 4,061
Std Dev 130
90% Lower Confidence 3,980

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 18-Oct-2019 stop 19-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192697F50	701992400002G	73	75	71	54	59	49	3,895	Y
	SCAD192697F52	701992400002G	73	75	71	54	59	49	4,200	Y
	SCAD192697F54	701992400002G	73	75	71	54	59	49	4,245	Y
	SCAD192697F51	701992400001N	73	75	71	54	59	49	3,995	Y
	SCAD192697F4F	701992400001N	73	75	71	54	59	49	4,170	Y
	SCAD192697F4C	701992400001N	73	75	71	54	59	49	3,980	Y
	SCAD192697F49	460192400003L	73	75	71	54	59	49	4,030	Y
	SCAD192697F4E	460192400003L	73	75	71	54	59	49	4,135	Y
	SCAD192697F4A	460192400003L	73	75	71	54	59	49	3,900	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.