



ISO/IEC 19752 Yield Test Report

MS510 Print Cartridge

Printer MS510

Declaration of Yield:	Average Cartridge Yield 1,500 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	---

Average 2,772
Std Dev 115
90% Lower Confidence 2,701

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	28-Apr-2012	30-Apr-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series(G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS12059115	4514PTB300749	4514PTB300749	71	73	70	46	56	43	2,784	Y
(S)CAS1205970D9	4514PTB300749	4514PTB300749	71	73	70	46	56	43	2,922	Y
(S)CAS12059709F	4514PTB300749	4514PTB300749	71	73	70	46	56	43	2,673	Y
(S)CAS12059710E	4514PTB300747	4514PTB300747	71	73	70	46	56	43	2,790	Y
(S)CAS12059710D	4514PTB300747	4514PTB300747	71	73	70	46	56	43	2,770	Y
(S)CAS1205970B1	4514PTB300747	4514PTB300747	71	73	70	46	56	43	2,691	Y
(S)CAS1205970DF	4514PTB300751	4514PTB300751	71	73	70	46	56	43	2,779	Y
(S)CAS1205970CF	4514PTB300751	4514PTB300751	71	73	70	46	56	43	2,954	Y
(S)CAS1205970BC	4514PTB300751	4514PTB300751	71	73	70	46	56	43	2,589	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.