

LEXMARK ISO/IEC 19752 Yield Test Report

MS510 Ship With Equipment Print Cartridge Printer MS510

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 7,646
Std Dev 270
90% Lower Confidence 7,478

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	30-Apr-2012	4-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg (F/C)	(F/C)	(F/C)	Avg	Max	Min		
(S)CAS120586A4D		4514PTB300749	71	73	70	53	58	49	8,081	Y
(S)CAS120586A16		4514PTB300749	71	73	70	53	58	49	7,641	Y
(S)CAS120586A86		4514PTB300749	71	73	70	53	58	49	7,735	Y
(S)CAS120586A6F		4514PTB300747	71	73	70	53	58	49	7,875	Y
(S)CAS120586A84		4514PTB300747	71	73	70	53	58	49	7,462	Y
(S)CAS120586A60		4514PTB300747	71	73	70	53	58	49	7,217	Y
(S)CAS120586A07		4514PTB300751	71	73	70	53	58	49	7,808	Y
(S)CAS120586A15		4514PTB300751	71	73	70	53	58	49	7,643	Y
(S)CAS120586A85		4514PTB300751	71	73	70	53	58	49	7,348	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.