



# ISO/IEC 19752 Yield Test Report

## MS521 Ultra High Yield Print Cartridge Printer MS521

Declaration of Yield: **Average Cartridge Yield 25,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 26,423  
**Std Dev** 431  
**90% Lower Confidence** 26,156

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date Tested</b>	25-Sep-2017	10-Oct-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS1717025AF	GSMPTB4600074	73	77	70	56	60	49	26,790	Y
SCAS1717025A1	GSMPTB4600074	73	77	70	56	60	49	25,639	Y
SCAS1717025B9	GSMPTB4600074	73	77	70	56	60	49	26,561	Y
SCAS17170259C	GSMPTB4600096	73	77	70	56	60	49	26,087	Y
SCAS1717025BC	GSMPTB4600096	73	77	70	56	60	49	26,763	Y
SCAS1717025B6	GSMPTB4600096	73	77	70	56	60	49	26,114	Y
CAS1717025B5	GSMPTB7017325	73	77	70	56	60	49	26,550	Y
CAS1717025BB	GSMPTB7017325	73	77	70	56	60	49	27,021	Y
CAS1717634D8F	GSMPTB7017325	73	77	70	56	60	49	26,281	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.