

MS521 Starter Toner Cartridge

Printer: MS521dn

Declaration of Yield:

Average Cartridge Yield	5,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 5,496
Std Dev 134
90% Lower
Confidence 5,412

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** **stop**
10-Aug-2017 14-Aug-2017

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake
Number of printers tested	No shake
Media used	Continuous
Paper feed orientation	3
Driver version	Hammermill Tidal MP - 20 lbs. - Letter
Operating system	Short Edge Feed (SEF)
Application software	Lexmark MS520 XL Series
Test page version	Windows 7 Professional
Power (off/on) everyday	Adobe Acrobat version 9
	ISO_IEC_19752_2004_Test_Page.pdf
	ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAS17170244D	GSMPTB4600074	73	77	70	56	60	49	5,615	Y
	SCAS17170244E	GSMPTB4600074	73	77	70	56	60	49	5,405	Y
	SCAS171702435	GSMPTB4600074	73	77	70	56	60	49	5,385	Y
	SCAS171702430	GSMPTB4600096	73	77	70	56	60	49	5,518	Y
	SCAS17170244F	GSMPTB4600096	73	77	70	56	60	49	5,395	Y
	SCAS171702433	GSMPTB4600096	73	77	70	56	60	49	5,279	Y
	SCAS171702441	GSMPTB7017325	73	77	70	56	60	49	5,632	Y
	SCAS17170244C	GSMPTB7017325	73	77	70	56	60	49	5,569	Y
	SCAS171702431	GSMPTB7017325	73	77	70	56	60	49	5,662	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.