

MS531 Toner Cartridge

Printer: MS531dw

Declaration of Yield:

Average Cartridge Yield	28,400	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 29,163
Std Dev 587
90% Lower Confidence 28,799

For questions concerning testing

contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	17-Nov-2022	1-Dec-2022

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake
Number of printers tested	No shake
Media used	Continuous
Paper feed orientation	3
Driver version	Hammermill Tidal MP - 20 lbs. - Letter
Operating system	Short Edge Feed (SEF)
Application software	Lexmark Printer Software G3 XL
Test page version	Windows 10 Enterprise
	Adobe Acrobat Reader DC ver. 2021.007.20099
	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAA22315000E	4602FST SCT107	72	72	72	45	45	45	29,636	Y
SCAA22315000A	4602FST SCT107	72	72	72	45	45	45	28,899	Y
SCAA223150011	4602FST SCT107	72	72	72	45	45	45	28,851	Y
SCAA223150014	7020FST NLE014	72	72	72	45	45	45	29,412	Y
SCAA223150010	7020FST NLE014	72	72	72	45	45	45	28,992	Y
SCAA22315000D	7020FST NLE014	72	72	72	45	45	45	28,982	Y
SCAA223150005	7020FST NLE033	72	72	72	45	45	45	29,375	Y
SCAA223150004	7020FST NLE033	72	72	72	45	45	45	30,209	Y
SCAA223150006	7020FST NLE033	72	72	72	45	45	45	28,113	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.