

LEXMARK TM ISO/IEC 19752 Yield Test Report

MS610 Extra High Yield Print Cartridge Printer MS610

Declaration of Yield:

Average Cartridge Yield 10,000 Standard Pages
Declared yield in accordance with ISO/IEC 19752

Average 11,867
Std Dev 587
90% Lower Confidence 11,504

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date Tested	14-May-2012	17-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS120586A18	4514PTB300198	72	75	68	45	50	40	11,420	Y
(S)CAS120586A1A	4514PTB300198	72	75	68	45	50	40	11,222	Y
(S)CAS120586A1C	4514PTB300198	72	75	68	45	50	40	12,377	Y
(S)CAS1205869AB	4514PTB300207	72	75	68	45	50	40	11,363	Y
(S)CAS1205869B7	4514PTB300207	72	75	68	45	50	40	11,193	Y
(S)CAS120586A1B	4514PTB300207	72	75	68	45	50	40	11,796	Y
(S)CAS1205869D3	4514PTB300608	72	75	68	45	50	40	12,618	Y
(S)CAS1205869D1	4514PTB300608	72	75	68	45	50	40	12,330	Y
(S)CAS1205869AA	4514PTB300608	72	75	68	45	50	40	12,487	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.