

# LEXMARK <sup>TM</sup> ISO/IEC 19752 Yield Test Report

## MS610 High Yield Print Cartridge Printer MS610

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>5,000</b>	<b>Standard Pages</b>
<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 6,451  
**Std Dev** 198  
**90% Lower Confidence** 6,329

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<b>start</b> 1-May-2012	<b>stop</b> 3-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series (G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
(S)CAS120586F79	4514PTB300608	71	73	70	53	56	49	6,568	Y
(S)CAS120586A88	4514PTB300608	71	73	70	53	56	49	6,457	Y
(S)CAS120586F84	4514PTB300608	71	73	70	53	56	49	6,325	Y
(S)CAS120586F8E	4514PTB300609	71	73	70	53	56	49	6,487	Y
(S)CAS120586F87	4514PTB300609	71	73	70	53	56	49	6,798	Y
(S)CAS120586A5	4514PTB300609	71	73	70	53	56	49	6,549	Y
(S)CAS120586F8F	4514PTB300611	71	73	70	53	56	49	6,516	Y
(S)CAS120586F43	4514PTB300611	71	73	70	53	56	49	6,148	Y
(S)CAS120586F44	4514PTB300611	71	73	70	53	56	49	6,214	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.