

MS63 Toner Cartridge

Printer: MS631dw/MS632dwe

Declaration of Yield:

Average Cartridge Yield	31,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 31,901
Std Dev 571
90% Lower Confidence 31,546

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 12-Sep-2022 **stop** 16-Sep-2022

Number of cartridges in testing	9	9
Qty. of cartridges used in calculation	9	9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark Printer Software G3 XL
Operating system		Windows 10 Enterprise
Application software		Adobe Acrobat Reader DC ver. 2021.007.20099
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD22161A728	4602FST SCT205	72	72	72	44	56	36	32,491	Y
SCAD22161A926	4602FST SCT205	72	72	72	44	56	36	32,232	Y
SCAD22161224C	4602FST SCT205	72	72	72	44	56	36	31,831	Y
SCAD22161A998	4602FST SCT170	72	72	72	44	56	36	31,602	Y
SCAD22161A853	4602FST SCT170	72	72	72	44	56	36	31,071	Y
SCAD221612240	4602FST SCT170	72	72	72	44	56	36	31,831	Y
SCAD22161A92A	7020FST NLE075	72	72	72	44	56	36	31,698	Y
SCAD22161A92E	7020FST NLE075	72	72	72	44	56	36	31,408	Y
SCAD221612235	7020FST NLE075	72	72	72	44	56	36	32,941	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.