

# LEXMARK ISO/IEC 19752 Yield Test Report

## MS710 Print Cartridge Printer MS710

Declaration of Yield: **Average Cartridge Yield 10,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 12,341  
**Std Dev** 311  
**90% Lower Confidence** 12,148

**For questions concerning testing contact**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<b>start</b> 6-Sep-2012	<b>stop</b> 10-Sep-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9.0
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS122383CAB	406322990000T	72	73	70	52	59	48	12,900	Y
(S)CAS122383CBE	406322990000T	72	73	70	52	59	48	12,413	Y
(S)CAS122383CB9	406322990000T	72	73	70	52	59	48	12,575	Y
(S)CAS122383C9D	4063229900009	72	73	70	52	59	48	12,249	Y
(S)CAS122383C9E	4063229900009	72	73	70	52	59	48	11,855	Y
(S)CAS122383CAA	4063229900009	72	73	70	52	59	48	12,180	Y
(S)CAS122383CA4	4063229900007	72	73	70	52	59	48	12,134	Y
(S)CAS122383C9F	4063229900007	72	73	70	52	59	48	12,176	Y
(S)CAS122383CA1	4063229900007	72	73	70	52	59	48	12,584	Y

**Comments and or exceptions:**

\*EOL was determined by the printer calling for the cartridge to be replaced.