

LEXMARK ISO/IEC 19752 Yield Test Report

MS710 High Yield Print Cartridge Printer MS710

Declaration of Yield: **Average Cartridge Yield 25,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 29,524
Std Dev 1,061
90% Lower Confidence 28,867

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 12-Sep-2012	<u>stop</u> 24-Sep-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9.0
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS122383C81	406322990000T	72	74	69	53	59	49	29,983	Y
(S)CAS122383C87	406322990000T	72	74	69	53	59	49	31,096	Y
(S)CAS122383C8B	406322990000T	72	74	69	53	59	49	29,297	Y
(S)CAS122383C85	4063229900009	72	74	69	53	59	49	28,454	Y
(S)CAS122383C7A	4063229900009	72	74	69	53	59	49	29,611	Y
(S)CAS122383C97	4063229900009	72	74	69	53	59	49	27,823	Y
(S)CAS122383C8C	4063229900007	72	74	69	53	59	49	29,504	Y
(S)CAS122383C83	4063229900007	72	74	69	53	59	49	30,930	Y
(S)CAS122383C82	4063229900007	72	74	69	53	59	49	29,022	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.