

LEXMARK ISO/IEC 19752 Yield Test Report

MS711 Print Cartridge Printer MS711

Declaration of Yield: **Average Cartridge Yield 10,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 12,382
Std Dev 187
90% Lower Confidence 12,266

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	start 6-Sep-2012	stop 10-Sep-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9.0
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS122383CBD	4063229900035	72	73	70	52	59	48	12,718	Y
(S)CAS122383CB4	4063229900035	72	73	70	52	59	48	12,364	Y
(S)CAS122383CAF	4063229900035	72	73	70	52	59	48	12,434	Y
(S)CAS122383CA0	406322990002T	72	73	70	52	59	48	12,584	Y
(S)CAS122383CB0	406322990002T	72	73	70	52	59	48	12,327	Y
(S)CAS122383CBC	406322990002T	72	73	70	52	59	48	12,144	Y
(S)CAS122383CAD	406322990002M	72	73	70	52	59	48	12,437	Y
(S)CAS122383CB8	406322990002M	72	73	70	52	59	48	12,177	Y
(S)CAS122383CAC	406322990002M	72	73	70	52	59	48	12,252	Y

Comments and or exceptions:

*EOL was determined by the printer calling for the cartridge to be replaced.