

# LEXMARK <sup>TM</sup> ISO/IEC 19752 Yield Test Report

## MS711 Extra High Yield Print Cartridge Printer MS711

Declaration of Yield: **Average Cartridge Yield 45,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average 47,532**  
**Std Dev 609**  
**90% Lower Confidence 47,155**

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 22-Sep-2012	<u>stop</u> 8-Oct-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS122383CE8	4063229900035	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	46,691	Y
(S)CAS122383CE4	4063229900035	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,105	Y
(S)CAS122383CE3	4063229900035	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,115	Y
(S)CAS122383CED	406322990002T	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,795	Y
(S)CAS122383CE0	406322990002T	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	48,420	Y
(S)CAS122383CE7	406322990002T	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,970	Y
(S)CAS122383CE9	406322990002M	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,293	Y
(S)CAS122383CE6	406322990002M	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	47,094	Y
(S)CAS122383CE5	406322990002M	71 / 21.6	73 / 22.7	70 / 21.1	52	56	50	48,309	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.