



ISO/IEC 19752 Yield Test Report

MS725 High Yield Print Cartridge

Printer: MS725

| | | | |
|-----------------------|--|---------------|-----------------------|
| Declaration of Yield: | Average Cartridge Yield | 15,000 | Standard Pages |
| | Declared yield in accordance with ISO/IEC 19752 | | |

Average 17,684
Std Dev 625
90% Lower Confidence 17,296

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

| | | |
|--|-----------------------------|--|
| Date Tested | <u>start</u> 30-Jan-2018 | <u>stop</u> 3-Feb-2018 |
| Number of cartridges in testing | | 9 |
| Qty. of cartridges used in calculation | | 9 |
| Shake Procedure | 1st shake 2nd shake | No Shake No Shake |
| Print mode | | Continuous |
| Number of printers tested | | 3 |
| Media used | | Hammermill Tidal MP - 20 lbs. - Letter |
| Paper feed orientation | | Short Edge Feed (SEF) |
| Driver version | | 47_G3 |
| Operating system | | Windows 7 Professional |
| Application software | | Adobe Acrobat version 9 |
| Test page version | | ISO_IEC_19752_2004_Test_Page.pdf |
| Power (off/on) everyday | | ON |

| Cartridge testing data: | Cartridge | Printer | Temperature | | | Humidity | | | Yield | Calculation |
|-------------------------|--------------|---------------|-------------|-----|-----|----------|-----|-----|--------|-------------|
| | | | Avg | Max | Min | Avg | Max | Min | | |
| | CAS1732100C5 | 4064PTBGLA175 | 74 | 76 | 73 | 50 | 52 | 48 | 17,107 | Y |
| | CAS1732100A6 | 4064PTBGLA175 | 74 | 76 | 73 | 50 | 52 | 48 | 18,153 | Y |
| | CAS1732100AE | 4064PTBGLA175 | 74 | 76 | 73 | 50 | 54 | 48 | 18,272 | Y |
| | CAS1732100C3 | 4064PTBGLA176 | 74 | 76 | 73 | 50 | 52 | 48 | 17,618 | Y |
| | CAS1732100A5 | 4064PTBGLA176 | 74 | 76 | 73 | 50 | 52 | 48 | 17,609 | Y |
| | CAS1732100B1 | 4064PTBGLA176 | 74 | 76 | 73 | 50 | 54 | 48 | 17,613 | Y |
| | CAS1732100B9 | 4064PTBGLA174 | 74 | 76 | 73 | 50 | 52 | 48 | 16,469 | Y |
| | CAS1732100C6 | 4064PTBGLA174 | 74 | 76 | 73 | 50 | 52 | 48 | 17,993 | Y |
| | CAS1732100F4 | 4064PTBGLA174 | 74 | 76 | 73 | 50 | 54 | 48 | 18,408 | Y |

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.