



ISO/IEC 19752 Yield Test Report

MS725 Extra High Yield Print Cartridge Printer MS725

Declaration of Yield:	Average Cartridge Yield	35,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 40,821
Std Dev 951
90% Lower Confidence 40,231

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 3-Feb-2018	<u>stop</u> 9-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210154	4064PTBGLA175	73	75	72	51	53	49	41,929	Y
CAS17321019C	4064PTBGLA175	73	75	72	51	53	49	41,793	Y
CAS17321013D	4064PTBGLA175	73	75	72	51	53	49	40,300	Y
CAS173210151	4064PTBGLA176	73	75	72	51	53	49	40,110	Y
CAS17321012E	4064PTBGLA176	73	75	72	51	53	49	41,072	Y
CAS173210138	4064PTBGLA176	73	75	72	51	53	49	39,365	Y
CAS17321014E	4064PTBGLA174	73	75	72	51	53	49	41,762	Y
CAS1732101A1	4064PTBGLA174	73	75	72	51	53	49	41,256	Y
CAS17321013F	4064PTBGLA174	73	75	72	51	53	49	39,804	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.