



# ISO/IEC 19752 Yield Test Report

## MS725 Ultra High Yield Print Cartridge Printer MS725

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>55,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 64,191  
**Std Dev** 2,559  
**90% Lower Confidence** 62,604

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date Tested</b>	16-Jan-2018	29-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1732101C8	4064PTBGLA175	72	75	65	52	64	48	65,405	Y
CAS173210224	4064PTBGLA175	73	76	72	51	53	48	69,342	Y
CAS1732101FF	4064PTBGLA175	73	75	73	50	54	48	66,051	Y
CAS1732101D9	4064PTBGLA176	72	75	65	52	64	48	61,357	Y
CAS173210230	4064PTBGLA176	73	76	72	51	53	48	64,172	Y
CAS1732101FB	4064PTBGLA176	73	75	73	50	54	48	62,893	Y
CAS1732101D6	4064PTBGLA174	72	75	65	52	64	48	61,052	Y
CAS17321022E	4064PTBGLA174	73	76	72	51	53	48	64,400	Y
CAS173210228	4064PTBGLA174	73	75	73	50	54	48	63,043	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.