



ISO/IEC 19752 Yield Test Report

MS810 Print Cartridge

Printer MS810

Declaration of Yield:
Average Cartridge Yield 10,000 Standard Pages
Declared yield in accordance with ISO/IEC 19752

Average 10,900
Std Dev 220
90% Lower Confidence 10,764

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	4-May-2012	6-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120545DDDF	4063127900002	4063127900002	74	78	69	40	48	37	10,815	Y
(S)CAS120545DE8	4063127900002	4063127900002	74	78	69	40	48	37	10,970	Y
(S)CAS120545DE0	4063127900002	4063127900002	74	78	69	40	48	37	10,615	Y
(S)CAS120545DEE	4063127900005	4063127900005	74	78	69	40	48	37	11,315	Y
(S)CAS120545DEC	4063127900005	4063127900005	74	78	69	40	48	37	10,835	Y
(S)CAS120545DF2	4063127900005	4063127900005	74	78	69	40	48	37	10,890	Y
(S)CAS120545DFF	4063127900010	4063127900010	74	78	69	40	48	37	10,920	Y
(S)CAS120545DEA	4063127900010	4063127900010	74	78	69	40	48	37	10,630	Y
(S)CAS120545DD8	4063127900010	4063127900010	74	78	69	40	48	37	11,110	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.