



## ISO/IEC 19752 Yield Test Report

### MS810 Print Cartridge

Printer MS810

Declaration of Yield: 
**Average Cartridge Yield 25,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 30,520  
**Std Dev** 1,792  
**90% Lower Confidence** 29,409

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

|  | <u>start</u> | <u>stop</u>                      |
|--|--------------|----------------------------------|
| <b>Date Tested</b>                     | 19-Jul-2012  | 9-Aug-2012                       |
| Number of cartridges in testing        |              | 9                                |
| Qty. of cartridges used in calculation |              | 9                                |
| Shake Procedure                        |              |                                  |
|  | 1st shake    | No Shake                         |
|  | 2nd shake    | No Shake                         |
| Print mode                             |              | Continuous                       |
| Number of printers tested              |              | 3                                |
| Media used                             |              | Orange Paper - 80gsm - A4        |
| Paper feed orientation                 |              | Short Edge Feed (SEF)            |
| Driver version                         |              | Gold 9                           |
| Operating system                       |              | Windows XP SP3                   |
| Application software                   |              | Acrobat version 9.1              |
| Test page version                      |              | ISO_IEC_19752_2004_Test_Page.pdf |

| Cartridge testing data: | Cartridge       | Printer       | Temperature |           |           | Humidity |     |     | Cartridge Yield | Cart used in Calculation |
|-------------------------|-----------------|---------------|-------------|-----------|-----------|----------|-----|-----|-----------------|--------------------------|
|                         |                 |               | Avg (F/C)   | Max (F/C) | Min (F/C) | Avg      | Max | Min |                 |                          |
|                         | (S)CAS1219231FC | 4063127900002 | 71          | 75        | 69        | 48       | 55  | 43  | 31,971          | Y                        |
|                         | (S)CAS1219231D1 | 4063127900002 | 71          | 75        | 69        | 48       | 55  | 43  | 32,168          | Y                        |
|                         | (S)CAS1219231DF | 4063127900002 | 71          | 75        | 69        | 48       | 55  | 43  | 30,673          | Y                        |
|                         | (S)CAS1219231F2 | 4063127900005 | 71          | 75        | 69        | 48       | 55  | 43  | 31,962          | Y                        |
|                         | (S)CAS1219231FA | 4063127900005 | 71          | 75        | 69        | 48       | 55  | 43  | 32,053          | Y                        |
|                         | (S)CAS1219231E0 | 4063127900005 | 71          | 75        | 69        | 48       | 55  | 43  | 31,189          | Y                        |
|                         | (S)CAS1219231F4 | 4063127900010 | 71          | 75        | 69        | 48       | 55  | 43  | 28,003          | Y                        |
|                         | (S)CAS1219231CC | 4063127900010 | 71          | 75        | 69        | 48       | 55  | 43  | 28,183          | Y                        |
|                         | (S)CAS1219231B  | 4063127900010 | 71          | 75        | 69        | 48       | 55  | 43  | 28,477          | Y                        |

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.